

## SecureSync® SAASM

### Secure and Rugged Time and Frequency Synchronization System



- SAASM available in GB-GRAM and MRU receivers
- Military signal P(Y) code SAASM GPS receiver and civil signal C/A-Code GPS receiver
- Robust Web-based user interface
- A wide variety of input/output signals supported
- Industry-leading low phase noise capability
- Modular (configure-to-order) ruggedized shock and vibration tested chassis
- Exceptional operating temperature range of -20°C to +65°C
- Hot start capable via DAGR/PLGR connectors
- Ethernet 10/100 Base-T
- Ultra-secure system with the latest network management tools
- Field-upgradable option cards
- IPv4/IPv6 dual stack
- Alert notifications via SNMP traps and e-mail alert
- Remote upgradable software
- IRIG time code generator (optional)
- 5-year limited warranty

SecureSync® SAASM combines Orolia's precision time and frequency technology with an ultra-secure Selective Availability Anti-Spoofing Module (SAASM)-based GPS receiver. This system was conceived specifically to satisfy the Joint Chiefs of Staff mandate that all newly-fielded Department of Defense GPS systems be SAASM-compliant (CJCSI 6130.01C: Enclosure E). SecureSync SAASM offers a choice between two SAASM receiver options: a 24-channel Miniature Ruggedized Unit (MRU) and a 12-channel Ground-Based GPS Receiver Application Module (GB-GRAM).

Mission-critical military applications will benefit from SecureSync SAASM's extreme reliability, security, and flexibility. An important advantage of SecureSync SAASM is its ruggedized shock and vibration-tested chassis, designed to meet MIL-STD-810F for environmental performance. The base unit provides an extremely accurate 1PPS timing signal aligned to a 10 MHz frequency signal without any 10 MHz phase discontinuity. An assortment of internal oscillator options is available to fulfill a broad range of requirements for holdover and phase noise.

The modular design enables a wide variety of highly specialized time and frequency functions. Up to 4 additional input/output modules can be added to each SecureSync SAASM to cater it to your specific needs. Choose from a vast selection of option cards to add to your configuration of timing signals, including additional 1PPS or time code (IRIG, ASCII, HaveQuick), frequency outputs (10 MHz, 5 MHz, 2.048 MHz, or 1.544 MHz), telecom T1/E1 data rates, multi-port NTP, and PTP. Modules can also be custom designed to meet the exact specifications of any military program.

SecureSync SAASM is a security-hardened network appliance designed to meet rigorous network security standards and best practices. It ensures accurate timing through multiple references, tamper-proof management, and extensive logging. Robust network protocols are used to allow for easy but secure configuration. Features can be enabled or disabled based on your network policies. Installation is aided by DHCP (IPv4), AUTOCONF (IPv6), and a front-panel keypad and display. The 1 RU chassis is powered by AC on an IEC60320 connector. DC power is also available as a primary source or as a back-up to standard AC power.



SAASM unit requires 2 option card slots for SAASM GPS module. Add up to 4 additional option modules in the remaining slots to get the features you need.

## Specifications

### System Performance

See option card descriptions for additional performance specifications.

#### 10 MHz Frequency Output:

	TCXO	OCXO	Low Phase Noise OCXO	Rubidium	Low Phase Noise Rubidium
Accuracy (average over 24 hours when GPS locked)	1x10 <sup>-11</sup>	2x10 <sup>-12</sup>	1x10 <sup>-12</sup>	1x10 <sup>-12</sup>	1x10 <sup>-12</sup>
Medium Term Stability (without GPS after 2 weeks of GPS lock)	1x10 <sup>-8</sup> /day	5x10 <sup>-10</sup> /day	2x10 <sup>-10</sup> /day	5x10 <sup>-11</sup> /month (3x10 <sup>-11</sup> /month typical)	5x10 <sup>-11</sup> /month (3x10 <sup>-11</sup> /month typical)
Short Term Stability (Allan Deviation)					
1 sec	2x10 <sup>-9</sup>	5x10 <sup>-10</sup>	5x10 <sup>-11</sup>	2x10 <sup>-11</sup>	5x10 <sup>-11</sup>
10 sec	1x10 <sup>-9</sup>	5x10 <sup>-11</sup>	2x10 <sup>-11</sup>	2x10 <sup>-12</sup>	2x10 <sup>-11</sup>
100 sec	3x10 <sup>-10</sup>	1x10 <sup>-11</sup>	1x10 <sup>-11</sup>	2x10 <sup>-12</sup>	5x10 <sup>-12</sup>
Temperature Stability (peak-to-peak)	1x10 <sup>-6</sup>	5x10 <sup>-9</sup>	1x10 <sup>-9</sup>	1x10 <sup>-10</sup>	1x10 <sup>-10</sup>
Phase Noise (dBc/Hz)					
@1 Hz	—	-95	-100	-80	-100
@10 Hz	—	-123	-128	-98	-128
@100 Hz	-110	-140	-148	-120	-148
@1 kHz	-135	-145	-153	-140	-153
@10 kHz	-140	-150	-155	-140	-155
Signal waveform and levels: +13 dBm into 50 ohm, BNC					

#### 1 PPS Output:

	TCXO	OCXO	Low Phase Noise OCXO	Rubidium	Low Phase Noise Rubidium
Accuracy to UTC (1-sigma locked to GPS)	±50 ns	±50 ns	±25 ns	±25 ns	±25 ns
Holdover (constant temp after 2 weeks of GPS lock)					
After 4 hours	12 µs	1 µs	0.5 µs	0.2 µs	0.2 µs
After 24 hours	450 µs	25 µs	10 µs	1 µs	1 µs
Signal waveform and levels: TTL (5V <sub>P-P</sub> ), into 50 ohm, BNC					

## Network Services

### Timing

- NTP v2, v3, v4: Conforms with or exceeds RFC1305 and 5905. Supports Unicast, Broadcast, Multicast, MD5 encryption, Peering, Stratum 2, Autokey
- SNTP v3, v4: Conforms with or exceeds RFC 1769, 2030, 4330, and 5905
- Time (RFC 868)
- Daytime (RFC 867)
- IEEE-1588v2 (PTP) via option card(s)
- NTP over Anycast

### Management

- IPv4/IPv6: Dual stack
- DHCPv4/DHCPv6 (AUTOCONF)/SLAAC: Automatic IP address assignment
- Authentication: LDAP, RADIUS, TACACS+
- Syslog: Logging
- SNMP: Supports v1, v2c, and v3 (no auth/auth/priv) with Enterprise MIB

### Communications

- HTTP: Browser-based configuration and monitoring
- Telnet: Remote configuration
- FTP Server: Access to files (logs, etc.)
- SMTP: Email

### Security Features

- Enable/Block Protocols
- Set SNMP community names and network access
- Password Protected
- Standard encryption/authentication protocols
- SSL Web-based Interface: SSL is used to secure HTTPS protocol to access configuration and status web pages.
- SSH: SSL and data compression technologies provide a secure and efficient means to control, communicate with, and transfer data to or from the time server remotely.
- SCP: Securely transfers files to and from the time server over an SSH session.
- SFTP: FTP replacement operates over an encrypted SSH transport
- SNMP v3: Remotely configure and manage over an encrypted connection
- Alert notifications via SNMP Traps and e-mail

## GPS SAASM Receivers

### GB-GRAM and MRU receivers

- Connector: Type N, +5V to power active antenna
- Receiver input: L1/L2, P(Y) code (PPS), SAASM GB-GRAM
- Tracking: GB-GRAM: 12 parallel, dual-frequency channels with RAIM (Receiver Autonomous Integrity Monitoring)  
MRU: 24 total channels (12 L1 and 12 L2) for simultaneous tracking
- Crypto Key input: DS-102. Compatible with AN/PYQ-10, AN/CYZ-10, KYK-13. Black/red key support. Front panel connector
- Security: SAASM GB-GRAM GPS PPS receiver
- Antenna/preamplifier: L1 1574.42 MHz & L2 1227.60 MHz, 40 dB gain (antenna sold separately)
- Acquisition time: Cold start <20 minutes (typical)

### Oscillator

- Standard Oscillator: OCXO
- Optional Oscillators: TCXO, Low Phase Noise OCXO (LPN OCXO), Rubidium (Rb), Low Phase Noise Rubidium (LPN Rb)

### Communications

#### Network Port

- RJ-45, 10/100 Base-T

#### Serial Set-up Interface

- RS-232 communications on DB-9 connector

#### Front Panel

- LED segments displays time
- Lockable keypad and configurable LCD display for network set-up
- Power/Status LEDs
- Zeroize flip switch and key fill

### Power

#### Choice of

- 100-240 VAC, 50/60 Hz, ±10% or 100-120 V<sub>AC</sub>, 400 Hz, ±10% from IEC60320 connector; power cord included
- 12-17 V<sub>DC</sub>, -15% to +20% or 21-60 V<sub>DC</sub>, -15% to +20%, secure locking device
- Auto-failover in the case of AC and DC

#### Power Draw

- TCXO: 40 W normal (50 W start-up)
- OCXO: 40 W normal (50 W start-up)
- Rb: 50 W normal (80 W start-up)
- LPN Rb: 52 W normal (85 W start-up)

### Environmental

	Operating	Storage	MIL-STD-810F
Temperature	-20 to +65°C (+55°C for Rb)	-40 to +85°C	
Humidity	0%-95% RH non-condensing @ 40°C		
Altitude	100-240 V <sub>AC</sub> up to 6,560 ft (2,000 m), 100-120 V <sub>AC</sub> up to 13,123 ft (4,000 M) 12-17 V <sub>DC</sub> and 21-60 V <sub>DC</sub> up to 13,123 ft (4,000 m)	45,000 ft (13,700 m)	
Shock	15g, 11ms half sine wave	50g, 11ms half sine wave <sup>1</sup>	516.5
Vibration	10-55Hz/0.07g <sup>2</sup> /Hz 55-500Hz/1.0g <sup>2</sup> /Hz	10-55Hz/0.15g <sup>2</sup> /Hz 55-500Hz/2.0g <sup>2</sup> /Hz	514.5

<sup>1</sup>SAASM GPS Storage Shock Specs: MRU 35g, GB-GRAM 40g

### Agency Approvals

CE, UL, cUL, CSA, FCC part 15 class A, ROHS, WEEE

### Physical & Environmental

#### Size/Weight

- Designed for EIA 19" rack. 16.75" W x 1.72" H (1U) x 14.33" D actual (425 mm W x 44 mm H x 364 mm D actual)
- Weight: 6.5 lbs. (2.95 kg) with Rubidium option; 6.0 lbs. (2.72 kg) without
- Rack mount hardware included (assembly required)

### Warranty

#### Five Year Limited Warranty<sup>1</sup>

- Oscillator for rubidium option is warranted for two years
- Extended warranty is available

<sup>1</sup>The warranty period may be dependent on country.

### Ordering Information

#### Base Units

#### 1200-XYZ

Select power, internal oscillator and GNSS reference options:

X=Power	Y=Internal Oscillator	Z=Primary Reference
0=AC 1=AC/DC (12 vdc) 2=AC/DC (24/48 vdc) 3=DC (12 vdc) 4=DC (24/48 vdc)	0=TCXO 1=OCXO 2=Low phase noise OCXO 3=Rubidium 5=Low phase noise Rb	5=SAASM GPS (MRU) <sup>1</sup> 7=SAASM GPS (GB-GRAM) <sup>1</sup>

#### Example

A SecureSync base unit with AC power, OCXO internal oscillator, and SAASM GPS (MRU) as the primary reference is Model Number 1200-015. It comes with a 10/100 Base-T network port and 1 each 1PPS and 10 MHz output signals. Order option modules for additional input/output functions.

<sup>1</sup>SAASM GPS option occupies 2 option modules. Only 4 additional option modules may be purchased.

### Option Modules

Up to 6 option modules can be accommodated per unit. The SAASM GPS module requires two card slots. See Option Module Card datasheet for details on additional option modules.

### Antenna

**8225S:** GPS SAASM Antenna

